



Series 2000 Gx5

For Power Generation
Continuous Applications
with air-to-air charge air
cooling

Engine Type	12V2000 G65	
Rated power ICXN	515 kW	691 bhp
Speed at rated power ICXN	1500 rpm	
Number of cylinders	12V - 90°	
Bore mm - in	130 mm	5.1 in
Stroke mm - in	150 mm	5.9 in
Displacement per cylinder I : cu - in	1.99 cu	121 in
Displacement, total I : cu - in	23.9 cu	1458 in
Fuel specification	EN 590, Grade No.1-D/2-D (ASTM D975-00)	

Engine Dimensions

12V2000 G65		
Dimensions (L x W x H) mm - in	1882 x 1580 x 1585 mm	74 x 62 x 62 in
Dry weight kg - lbs	2490 kg	5490 lbs

Engine Type	16V2000 G65	
Rated power ICXN	655 kW	878 bhp
Speed at rated power ICXN	1500 rpm	
Number of cylinders	16V - 90°	
Bore mm - in	130 mm	5.1 in
Stroke mm - in	150 mm	5.9 in
Displacement per cylinder I : cu - in	1.99 cu	121 in
Displacement, total I : cu - in	31.8 cu	1944 in
Fuel specification	EN 590, Grade No.1-D/2-D (ASTM D975-00)	

Engine Dimensions

16V2000 G65		
Dimensions (L x W x H) mm - in	2226 x 1580 x 2015 mm	88 x 62 x 79 in
Dry weight kg - lbs	3150 kg	6835 in

Engine Type	18V2000 G65	
Rated power ICXN	720 kW	966 bhp

Speed at rated power ICXN	1500 rpm	
Number of cylinders	18V - 90°	
Bore mm - in	130 mm	5.1 in
Stroke mm - in	150 mm	5.9 in
Displacement per cylinder l : cu - in	1.99 cu	121 in
Displacement, total l : cu - in	35.8 cu	2185 in
Fuel specification	EN 590, Grade No.1-D/2-D (ASTM D975-00)	

Engine Dimensions

18V2000 G65

Dimensions (L x W x H) mm - in	2400 x 1780 x 2015 mm	95 x 70 x 79 in
Dry weight kg - lbs	3500 kg	7715 lbs